




CLM - 1 PRODUCT DATA

GENERAL DESCRIPTION

The **SUPERIOR® Series CLM-1 Gas Chlorinator** is a state-of-the-art, vacuum-operated, solution feed type which mounts directly on a chlorine cylinder valve. The chlorinator is mounted onto the chlorine cylinder valve using a very heavy-duty, positive yoke clamp connection. A chlorine gas flow meter, mounted directly onto the vacuum regulator, indicates the amount of chlorine being fed. Chlorine flow rate is manually adjusted and the design permits easy addition of a number of automatic flow rate control devices. A high efficiency, water operated ejector produces the vacuum necessary to operate the system. The ejector assembly contains a unique back-flow check valve system to prevent pressurized water from entering the chlorinator. A spring-opposed diaphragm vacuum regulator controls the chlorine gas flow rate and also acts as the safety shut-off valve.

CLM-1 TYPICAL INSTALLATION




FEATURES

The SUPERIOR™ Series CLM-1 represents the most modern design technology coupled with the very best materials available to create an outstanding, user friendly piece of equipment. It is designed with user safety as a primary concern.

1. A new ultra-thick, fluoroplastic yoke coating gives SUPERIOR™ corrosion resistance, won't crack, peel or chip. Chlorine will not diffuse through it to cause coating bubbling and peeling.
2. All molded parts are fiber-glass reinforced ABS plastic, designed for SUPERIOR™ strength, warp-resistance and chlorine resistance.
3. The rate valve "Seat" is pure fluoroplastic and will not swell, stick or become brittle with age or exposure to liquid chlorine.
4. All external bolts and nuts are Titanium for complete corrosion resistance..a SUPERIOR™ exclusive. There are no stainless steel or monel nuts and bolts to corrode and freeze up in the presence of moist chlorine gas.
5. Extra heavy-duty outlet threads on the ejector diffuser prevents accidental breakage from over-tightening or "bumping" of the ejector assembly.
6. The "Universal" ejector diffuser allows use of high pressure solution hose, direct ejector mounting in mains, or in-line piping with rigid solution pipe.
7. Easier to service and perform routine maintenance, with standard size wrench lugs provided on all screwed-together ejector parts. No more pipe wrenches to accidentally tear and scrape plastic surfaces.
8. All vacuum fitting holes are heavily reinforced to prevent the possibility of cracking from over-tightening fittings.
9. "Dual-pressure" check valve is standard on all SUPERIOR™ gas Chlorinators. Proven high back-pressure unitized check valve design protects against sudden surges up to 300 PSIG while a spring-loaded diaphragm check provides positive shutoff even when there is no back-pressure to force the seat closed.
10. PVDF vacuum tubing fittings are standard..another SUPERIOR™ exclusive. "User friendly" design makes it easy to attach tubing and to tighten or loosen ferrule nuts without tools.
11. Fewer parts, combined with superior materials and a superior design gives you a SUPERIOR™ Gas Chlorinator.

CLM-1 FLOW DIAGRAM



FLOW METER CAPACITIES

Variable area flow metering tubes are available with dual English/Metric scale maximum capacities of 0.8, 1.5, 4, 10, 25, 50 and 100 pounds per 24 hours of chlorine gas, as well as 15, 30, 75, 200, 500, 1000 and 2000 grams per hour, respectively. All metering tubes are interchangeable and may be changed in the field without special tools.

MODULAR DESIGN

SUPERIOR™ Gas Chlorinators have been designed to give maximum flexibility in system installation. The vacuum regulator and metering tube panel are close coupled and mounted onto the chlorine cylinder valve as a single assembly. The ejector can be located wherever plumbing and/or hydraulic conditions make it most desirable. Modular design also makes it easy and inexpensive to expand or upgrade the system. The metering tube panel may be detached from the vacuum regulator at any time, in just a few minutes, if future requirements or safety dictate a remote metering application, or multiple point chlorination is desired.

MATERIALS OF CONSTRUCTION

One of SUPERIOR™'s major competitive advantages is the use of the finest, strongest and most durable materials available. Extensive use of Fluoroplastics and fiberglass reinforced thermoplastics allow SUPERIOR™ Gas Chlorinators to withstand attack by chlorine in any form and to give the longest operational life. Many parts are guaranteed for the life of the equipment against chlorine damage.

SYSTEM OPERATION

The vacuum regulator is securely clamped onto the chlorine cylinder valve. Water under pressure flows through the ejector at high velocity which causes a strong vacuum to be created. This opens the check valves in the ejector assembly and transmits a vacuum signal through the meter tube/rate valve panel back to the vacuum regulator. When the vacuum reaches a pre-set level, the diaphragm in the regulator moves to open the chlorine inlet safety valve, permitting gas to flow from the chlorine cylinder. The spring-opposed diaphragm and inlet valve regulate the vacuum at this point.

Chlorine gas passes through the flow meter panel and rate control valve to the ejector. The gas mixes with the ejector water and is discharged through the diffuser into the water being treated.

SPECIFICATIONS

The chlorinator shall be SUPERIOR™ MODEL CLM-1 manufactured by Chemical Injection Technologies, Inc., Ft. Pierce, Florida, and shall have a maximum capacity of _____ pounds per day (gr/hr) of chlorine feed and shall be equipped with a chlorine flow meter of _____ pounds per day (gr/hr).

The chlorinator shall consist of a close-coupled vacuum regulator/flow meter, and ejector/check valve. Each of these assemblies shall be capable of being individually located wherever safety and/or operator convenience dictates. The vacuum regulator/flow meter assembly shall be capable of being separated into independant vacuum regulator and metering panel assemblies at any time for remote metering or multiple point applications.

The vacuum regulator/flow meter assembly shall mount directly on the cylinder valve by means of a positive yoke type clamp having an integral tightening screw with slide bar handle. No wrenches or other tools shall be required to mount or dismount the vacuum regulator from the cylinder. The cylinder valve/chlorinator inlet adaptor shall be constructed of corrosion-proof fluoroplastic material which shall be inert to the effects of wet, dry or liquid chlorine. The inlet safety shut-off/vacuum regulating valve shall be of capsulated design, easily removable as a unit from the outlet side of the yoke. A fluoroplastic filter shall be installed in the vacuum regulator inlet and shall be capable of removing impurities greater than 25 microns. A pressure relief valve shall be incorporated into the vacuum regulator to prevent pressure from building up in the system. All external screws and nuts shall be made of Titanium to prevent corrosion.

The vacuum regulator/flow meter bodies shall be constructed of fiberglass reinforced thermoplastic material and shall incorporate a flow rate control valve made of fluoroplastic material which is inert to the corrosive effects of chlorine. The rate valve metering tip shall be constructed of metal which is completely impervious to the effects of wet, dry or liquid chlorine attack. Design shall provide for full closing of the rate valve without engaging the control surfaces, to prevent damage. Minimum calibrated feed rate shall be 1/20th of maximum flow meter scale (20:1 turndown ratio). Accuracy shall be ±2% of maximum.

Vacuum shall be created by a fixed-throat venturi/ejector system connected directly to the chlorine solution diffuser. A dual high-pressure/low-pressure check valve system shall prevent water from entering the gas system. The ejector assembly shall be capable of withstanding water pressure up to 300 PSIG (20.7 Bars). A universal-type chlorine solution diffuser shall be provided which shall allow close-coupling of the ejector to a water main, use of flexible solution hose or rigid solution pipe without the use of special adaptors.

SPECIFICATIONS STANDARD ACCESSORIES

25 ft -3/8" Vacuum tubing
10 - Lead cylinder connection gaskets
1 - Cylinder Wrench
2 - Vent insect screens

OPTIONAL ACCESSORIES AVAILABLE

Inlet Water Assembly	Gas Masks
Wall Manifold Kits	Gas Detectors
Booster Pumps	Scales
Residual Analyzers	Gauges
Automatic Controls	Chlorine Comparators
Ton Container Adaptors	Ball Check Valve
Dual High Pressure Check Valve Assembly	
Floor Cabinets	Chlor-Clear & More

OTHER SUPERIOR™ SOLUTIONS AVAILABLE

VACUFEED LIQUID CHEMICAL FEED SYSTEMS
VACUUM ALARM SAFETY DEVICE
INSTRUMENTATION, ANALYZERS, & CONTROLS
CHLOR-CLEAR EDUCTOR TUBE CLEARING SYSTEM
UP TO 10,000 POUNDS PER DAY (00 KG/HR)
GAS SULFONATORS (DECHLORINATOR)
AMMONIATORS
AUTOMATIC FLOW PROPORTIONING
AUTOMATIC RESIDUAL CONTROL



SUPERIOR™ Gas Chlorinators are proudly made by Chemical Injection Technologies, Inc. 835 Edwards Road, Fort Pierce, Florida 34982 USA. T: 772-461-0666.